

SPECIFICATIONS


Electrical

- Current Rating: 1A AC, DC
- Voltage Rating: 50V AC/ max.
- Operating Temp.: -25°C ~ +85°C
- Insulation Resistance: 500MΩ/ min.
- Dielectric Withstanding Voltage: 500V AC/ min.
- Contact Resistance: 20mΩ/ max.

Material

Material: PBT, UL94V-0

Poles	Dimension mm		Part No.
	A	B	
20	9.00	13.00	LH-SHD100-2×10
30	14.00	18.00	LH-SHD100-2×15
40	19.00	23.00	LH-SHD100-2×20
50	24.00	28.00	LH-SHD100-2×25

公意/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名(Title):		 鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
.XX ±0.2 .X ±0.3			比例/Scale Free	1.0mm Wire-to-Board Housing Dual Row		
A0	NEW DRAWING	2018.08.09	Size A4	料號/Part No:	圖號/Drawing No:	核准/APPD: Joe
REV	概述/REVISION	日期/DATE		LH-SHD100-2×XX	1000D-2×XX	審核/CHKD: Joe
						製圖/DR: Mandy
						張數/Sheet 1 of 1
						REV. A0