



SPECIFICATIONS

Current Rating: 3A AC, DC
 Voltage Rating: 250 AC Maximum
 Operating Temp: -25°C ~ + 85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material: Nylon 66, UL94V-2

Poles	Dimension mm (in.)		Part No.
	A	B	
2	2.54 (0.100)	5.64 (0.222)	LH-MX254-02
3	5.08 (0.200)	8.16 (0.321)	LH-MX254-03
4	7.62 (0.300)	10.72 (0.422)	LH-MX254-04
5	10.16 (0.400)	13.30 (0.524)	LH-MX254-05
6	12.70 (0.500)	15.78 (0.621)	LH-MX254-06
7	15.24 (0.600)	18.40 (0.724)	LH-MX254-07
8	17.78 (0.700)	20.80 (0.819)	LH-MX254-08
9	20.32 (0.800)	23.50 (0.925)	LH-MX254-09
10	22.86 (0.900)	26.00 (1.024)	LH-MX254-10
11	25.40 (1.000)	28.50 (1.122)	LH-MX254-11
12	27.94 (1.100)	31.00 (1.220)	LH-MX254-12
13	30.48 (1.200)	33.50 (1.319)	LH-MX254-13
14	32.02 (1.300)	36.00 (1.417)	LH-MX254-14
15	35.56 (1.400)	38.50 (1.516)	LH-MX254-15
16	38.10 (1.500)	41.20 (1.622)	LH-MX254-16
17	40.64 (1.600)	43.60 (1.717)	LH-MX254-17
18	43.18 (1.700)	46.32 (1.824)	LH-MX254-18
20	48.26 (1.900)	51.34 (2.021)	LH-MX254-20

PART NO.:
LH-MX 254 - XX

No.Of Contact: 02~20
 Pitch: 2.54mm
 Housing Series No.

公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名(Title):	2.54mm Wire-to-Board Housing	鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL: (02) 8228-6487 FAX: (02) 8228-6486
X.XX ±0.25 X.X ±0.35			比例/Scale Free	料號/Part No:		
A0	NEW DRAWING	2018.08.16	Size A4	圖號/Drawing No:	2510-XX	核對/APPD. Joe
REV	概述/REVISION	日期/DATE				製圖/DR. Mandy
						報數/Sheet 1 of 1
						REV. A0