



SPECIFICATION:

- Poles: 4~30.
- Voltage rating: AC, DC, 50V(50HZ).
- Current rating: 0.4A, AC/DC.
- Withstand voltage: 200V AC/minutes.
- Working Temperature: -25°C ~ +85°C.
- Insulation resistance: >500MΩ.
- Contact resistance: <0.02Ω.
- Terminal mtr'l: Phosphor Bronze.
- Housing mtr'l: PA9T, UL94V-0
- Housing color: Black.

NO. of Contacts (n)	Dimensions		
	A	B	C
4	3.0	5.10	7.0
5	4.0	6.10	8.0
6	5.0	7.10	9.0
7	6.0	8.10	10.0
8	7.0	9.10	11.0
9	8.0	10.10	12.0
10	9.0	11.10	13.0
11	10.0	12.10	14.0
12	11.0	13.10	15.0
13	12.0	14.10	16.0
14	13.0	15.10	17.0
15	14.0	16.10	18.0
16	15.0	17.10	19.0
17	16.0	18.10	20.0
18	17.0	19.10	21.0
19	18.0	20.10	22.0
20	19.0	21.10	23.0
21	20.0	22.10	24.0
22	21.0	23.10	25.0
23	22.0	24.10	26.0
24	23.0	25.10	27.0
25	24.0	26.10	28.0
26	25.0	27.10	29.0
27	26.0	28.10	30.0
28	27.0	29.10	31.0
29	28.0	30.10	32.0
30	29.0	31.10	33.0

※ 需求7PIN者,請洽我司業務.

SERIES NO.	PIN type	Pin no.	Plating	Packing	Pin 1 Location
LFPC-K810DL	SV	XX	PT	X	X
FPC 1.00mm pitch NON-ZIF Dual contact	SV: SMT Vertical	4~36 Pins	PT: Tin G1: Gold Flash	1: Tube 2: Tape/Reel 3: T/R&Malar	N: Normal type R: Reverse type

公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		單位/Unit mm	品名/Title :
.X	±0.35	比例/Scale	FPC1.0Pitch SMD Vertical Dual Contact type Non-ZIF
.XX	±0.20	Free	料號/Part No :
ANG.	±3°	Size A4	圖號/Drawing No :
A0	NEW DRAWING	2018.06.18	LFPC-K810DL-SV-XX-XX-X-X
REV	概述/REVISION	日期/DATE	


鍊亨電子有限公司
 LAI HENG TECHNOLOGY LTD.
 TEL: (02) 8228-6487 FAX: (02) 8228-6486
 核加/APPD. 7/4 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1 REV. A0