



1. Material

- 1.1: Housing: PA46, UL94-V0, Color: Natural.
- 1.2: Contact: C5191-H, T=0.20±0.01.
- 1.3: LEG: C2680-H, T=0.25±0.01.

2. Plating

- 2.1: Contact: Gold flash over Nickel.
- 2.2: LEG: Gold flash over Nickel.

3. Rating:

- 3.1: Operating Voltage: 50V AC/DC.
- 3.2: Current Rating: 0.5A AC/DC.
- 3.3: Operating Temperature: -40°C ~ +80°C.

4. Pater Number:

LFPC 05 11-XX R-TAG

- PLATING: Gold Flash
- PACKAGING T&R (3000 PCS/REEL)
- RIGHT ANGLE (DOUBLE-FACE CONTACT)
- NO.OF CONTACTS
- SERIE NUMBER: H=1.2mm.
- PITCH=0.5MM
- FPC SERIES

PORT NO	Dimension		
	A	B	D
06P	5.10	4.25	3.60
08P	6.10	5.25	4.60
10P	7.10	6.25	5.60
12P	8.10	7.25	6.60
14P	9.10	8.25	7.60
16P	10.10	9.25	8.60

REV	概述/REVISION	日期/DATE
A0	NEW DRAWING	2018.05.25

公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
.X	±0.35
.XX	±0.15
.XXX	±0.05

單位/Unit	品名(Title):
mm	FPC 0.5Pitch 1.2H SMD 臥式 雙接觸
比例/Scale	Non-ZIF 鍍金 (T&R)
Free	料號/Part No:
Size	LFPC0511-XXR-TAG

圖號/Drawing No:



鍊亨電子有限公司
LAI HENG TECHNOLOGY LTD.
TEL: (02) 8228-6487 FAX: (02) 8228-6486

核准/APPD.	審核/CHKD.	製圖/DR.	張數/Sheet	REV.
Joe	Joe	Mandy	1 of 1	A0