



SPECIFICATION

Current Rating: 1 A
 Withstanding Voltage: 500V AC
 Insulation Resistance: 1000 Megohms Min.
 Operating Temperature: -55°C to +105°C

MATERIAL

Contact: Copper Alloy
 Insulator: Polyester, UL94V-0
 NYLON 6T
 Plating: All Gold or Tin

ORDER INFORMATION

LP/H 127 T X N a A c - 3.5 - 1xXX XT

Pitch: 1.27mm Type T:SMT

Material N: NYLON 6T

other
 AT: A Type
 BT: B Type

Contact Plating
 T : Tin
 G : Gold Flash
 G3 : All Gold 3u"
 G5 : All Gold 5u"
 G10: All Gold 10u"
 G15: All Gold 15u"
 G20: All Gold 20u"
 G30: All Gold 30u"

No.Of Contact
 Single Row: 1x02~1x50

SMT Expand Size:
 Standard: 3.5

a: Pin Chart Dimension See Pin Chart
 A: Insulation Height: 1.0mm, Width: 2.1mm
 c: Pin Chart Dimension See Pin Chart
 Standard: 3A1.2

Pin Chart:

a : _____ mm
 Standard: 3.0mm

c : _____ mm
 Standard: 1.2 mm

公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		單位/Unit mm	品名/Title :
		比例/Scale	1.27mm Pin Header H:1.0 W:2.1 Single Row SMT Type
A0	NEW DRAWING	2018.08.16	料號/Part No :
REV	概述/REVISION	日期/DATE	圖號/Drawing No :

單位/Unit mm	品名/Title :
比例/Scale	1.27mm Pin Header H:1.0 W:2.1 Single Row SMT Type
Free Size	料號/Part No :
A4	圖號/Drawing No :

鍊亨電子有限公司
 LAI HENG TECHNOLOGY LTD.
 TEL:(02) 8228-6487 FAX:(02) 8228-6486

核加/APPD.	審核/CHKD.	製圖/DR.	張數/Sheet	REV.
7/6	Joe	Mandy	1 of 1	A0