

SPECIFICATION

Current Rating: 1 A
 Withstanding Voltage: 500V AC
 Insulation Resistance: 1000 Megohms Min.
 Operating Temperature: -55°C to +105°C

MATERIAL

Contact: Coppery Alloy
 Insulator: NYLON 6T, UL94V-0
 Plating: All Gold or Tin

ORDER INFORMATION

LP/H 127 S X N a E c E b - 1xXX

Pitch: 1.27mm Type S: 180°

Material N: NYLON 6T

No. Of Contact Single Row: 1x02~1x50

Contact Plating

- T : Tin
- G : Gold Flash
- G3 : All Gold 3u"
- G5 : All Gold 5u"
- G10: All Gold 10u"
- G15: All Gold 15u"
- G20: All Gold 20u"
- G30: All Gold 30u"

a: Pin Chart Dimension See Pin Chart
 A: Insulation Height: 2.5mm, Width: 2.1mm
 c: Pin Chart Dimension See Pin Chart
 A: Insulation Height: 1.0mm, Width: 2.1mm
 b: Pin Chart Dimension See Pin Chart

Standard: 3A1A2.3

Pin Chart:

a : _____ mm


Standard: 3.0mm

b : _____ mm


Standard: 2.3mm

c : _____ mm

Standard: 1.0mm



Recommended P.C.Board Hold Layout

公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名/Title :	1.27mm Pin Header H:2.5 W:2.1 Single Row Dual Base Straight Dip Type	 鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
A0	NEW DRAWING	2018.08.16	比例/Scale Free	料號/Part No :		
REV	概述/REVISION	日期/DATE	Size A4	圖號/Drawing No :	127-GSD-1×XX-ABC-0-3	核加/APPD. 740 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1 REV. A0