



SPECIFICATION

Current Rating: 1 A  
 Withstanding Voltage: 500V AC  
 Insulation Resistance: 1000 Megohms Min.  
 Operating Temperature: -55°C to +105°C (NYLON 6T)

MATERIAL

Contact: Copper Alloy  
 Insulator: Polyester, UL94V-0  
 NYLON 6T  
 Plating: All Gold or Tin



ORDER INFORMATION


LP/H 200 R X N a B c / b - 2xXX  
 Pitch: 2.0mm Type R: 90° Material N: NYLON 6T  
 No. Of Contact Dual Row: 2x02~2x40

Contact Plating

T : Tin  
 G : Gold Flash  
 G3 : All Gold 3u"  
 G5 : All Gold 5u"  
 G10: All Gold 10u"  
 G15: All Gold 15u"  
 G20: All Gold 20u"  
 G30: All Gold 30u"

a: Pin Chart Dimension See Pin Chart  
 B: Insulation Height: 1.5mm, Width: 4.0mm  
 c: Pin Chart Dimension See Pin Chart  
 b: Pin Chart Dimension See Pin Chart


Standard: 4B1/2.8



Recommended P.C.Board Hold Layout

Pin Chart:

a : \_\_\_\_\_ mm  
 Standard: 4.0mm  
 b : \_\_\_\_\_ mm  
 Standard: 2.8mm  
 c : \_\_\_\_\_ mm  
 Standard: 1.0mm

公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名/Title : 2.0mm Pin Header H:1.5 W:4.0 Dual Row Down Angle Dip Type	 <b>鍊亨電子有限公司</b> LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
A0	NEW DRAWING	2018.08.16	比例/Scale Free	料號/Part No : LP/H200RXNaBc/b-2×XX	
REV	概述/REVISION	日期/DATE	Size A4	圖號/Drawing No : 200-GR1-2×XX-ABC-N(H1.5)	核加/APPD. 740 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1 REV. A0