

Recommended P.C.Board
Hold Layout

SPECIFICATION

Current Rating: 1 A
 Withstanding Voltage: 500V AC
 Insulation Resistance: 1000 Megohms Min.
 Operating Temperature: -40°C to +85°C (PBT)
 -55°C to +105°C (NYLON 6T)

MATERIAL

Contact: Copper Alloy
 Insulator: Polyester, UL94V-0
 NYLON 6T or PBT
 Plating: All Gold or Tin

ORDER INFORMATION

LP/H 200 R X X a A d A c / b - 1xXX

Pitch: 2.0mm Type R: 90°

Material P: PBT N: NYLON 6T

No. Of Contact Single Row: 1x01~1x40

a: Pin Chart Dimension See Pin Chart
 A: Insulation Height: 2.0mm, Width: 2.0mm
 d: Pin Chart Dimension See Pin Chart
 A: Insulation Height: 2.0mm, Width: 2.0mm
 c: Pin Chart Dimension See Pin Chart
 b: Pin Chart Dimension See Pin Chart

Standard: 4A0A1/2.8

Pin Chart:

Contact Plating

a : _____ mm

Standard: 4.0mm

b : _____ mm

Standard: 2.8mm


c : _____ mm

Standard: 1.0mm

d : _____ mm

Standard: 0.0mm

T : Tin
 G : Gold Flash
 G3 : All Gold 3u"
 G5 : All Gold 5u"
 G10 : All Gold 10u"
 G15 : All Gold 15u"
 G20 : All Gold 20u"
 G30 : All Gold 30u"

公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名/Title : 2.0mm Pin Header H:2.0 W:2.0 Single Row Dual Base Down Angle Dip Type	 鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
A0	NEW DRAWING	2018.08.16	比例/Scale Free	料號/Part No : LP/H200RXXaAdAc/b-1×XX	
REV	概述/REVISION	日期/DATE	Size A4	圖號/Drawing No : 200-GR1D-1×XX-ABCD-X	核加/APPD. 740 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1 REV. A0