

Recommended P.C.Board  
Hold Layout

SPECIFICATION

Current Rating: 1 A  
 Withstanding Voltage: 500V AC  
 Insulation Resistance: 1000 Megohms Min.  
 Operating Temperature: -55°C to +105°C (NYLON 6T)

MATERIAL

Contact: Copper Alloy  
 Insulator: Polyester, UL94V-0  
 NYLON 6T  
 Plating: All Gold or Tin

ORDER INFORMATION

LP/H 200 S X N a B b - 1xXX

Pitch: 2.0mm Type S: 180°

Material N: NYLON 6T

No. Of Contact  
 Single Row: 1x01~1x40

a: Pin Chart Dimension See Pin Chart  
 B: Insulation Height: 1.5mm, Width: 2.0mm  
 b: Pin Chart Dimension See Pin Chart

Standard: 4B2.8

Contact Plating  
 T : Tin  
 G : Gold Flash  
 G3 : All Gold 3u"  
 G5 : All Gold 5u"  
 G10: All Gold 10u"  
 G15: All Gold 15u"  
 G20: All Gold 20u"  
 G30: All Gold 30u"


Pin Chart:

a : \_\_\_\_\_ mm

Standard: 4.0mm

b : \_\_\_\_\_ mm

Standard: 2.8mm

公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名/Title :	 <b>鍊亨電子有限公司</b> LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
			比例/Scale Free	2.0mm Pin Header H:1.5 W:2.0 Single Row Straight Dip Type	
A0	NEW DRAWING	2018.08.16	料號/Part No :	圖號/Drawing No :	核加/APPD. 740
REV	概述/REVISION	日期/DATE	Size A4	LP/H200SXNaBb-1×XX	200-GS-1×XX-AB-N(H1.5)
					審核/CHKD. Joe
					製圖/DR. Mandy
					張數/Sheet 1 of 1
					REV. A0