



Recommended P.C.Board
Hold Layout

SPECIFICATION

Current Rating: 1 A
 Withstanding Voltage: 500V AC
 Insulation Resistance: 1000 Megohms Min.
 Operating Temperature: -40°C to +85°C (PBT)
 -55°C to +105°C (NYLON 6T)

MATERIAL

Contact: Copper Alloy
 Insulator: Polyester, UL94V-0
 NYLON 6T or PBT
 Plating: All Gold or Tin

ORDER INFORMATION

LP/H 200 S X X a A c A b - 1xXX

Pitch: 2.0mm Type S: 180°

Material P: PBT N: NYLON 6T

No. Of Contact Single Row: 1x01~1x40

Contact Plating

T : Tin
 G : Gold Flash
 G3 : All Gold 3u"
 G5 : All Gold 5u"
 G10 : All Gold 10u"
 G15 : All Gold 15u"
 G20 : All Gold 20u"
 G30 : All Gold 30u"

a: Pin Chart Dimension See Pin Chart
 A: Insulation Height: 2.0mm, Width: 2.0mm
 c: Pin Chart Dimension See Pin Chart
 b: Pin Chart Dimension See Pin Chart

Standard: 4A0A2.8

Pin Chart:

a : _____ mm

Standard: 4.0mm

b : _____ mm

Standard: 2.8mm

c : _____ mm

Standard: 0.0mm

公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名/Title :	2.0mm Pin Header H:2.0 W:2.0 Single Row Dual Base Straight Dip Type			
			比例/Scale	料號/Part No :	LP/H200SXXaAcAb-1×XX			
A0	NEW DRAWING	2018.08.16	Free Size A4	圖號/Drawing No :	200-GSD-1×XX-ABC-X			
REV	概述/REVISION	日期/DATE		核加/APPD. 740	審核/CHKD. Joe	製圖/DR. Mandy	張數/Sheet 1 of 1	REV. A0


鍊亨電子有限公司
 LAI HENG TECHNOLOGY LTD.
 TEL:(02) 8228-6487 FAX:(02) 8228-6486