



Part No.
LSIP 1778 M - 1 x XX GO

Plating: Gold Flashed
 No. of Contacts:
 Single Row: 1x01~1x40
 M: Machined Pin Header
 1.778mm Pitch
 Series No.

Technical Data

Material:

- Insulator body(housing): PBT (black /UL 94V-0)
- Pin :Brass, machined,
- Plating:Gold plated:>40u"nickel/G-F(0.4~1u")

Electrical

- Current rating: 3 Amps/contact max
- Operating :60 Veff
- Insulation resistance:>1000 MΩ at =100V

Mechanical:

- Operating temperature: Gold platde: -55°C to + 125°C (continuous) Tin plated: -40°C to +105°C
- Soldering temperature: + 260°C ,10s max

			公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	單位/Unit mm	品名/Title :
				比例/Scale	1.778MM Michined Pin Header Single Row (Gold Plated)
A0	NEW DRAWING	2018.10.05		Free	料號/Part No :
REV	概述/REVISION	日期/DATE		Size A4	LSIP1778M-1×XX GO

			圖號/Drawing No :
			ILMSXX-G12/1.778(S100-G12)

鍊亨電子有限公司
 LAI HENG TECHNOLOGY LTD.
 TEL:(02) 8228-6487 FAX:(02) 8228-6486

核准/APPD. 7/0 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1

REV. A0