



RECOMMENDED PCB LAYOUT

PIN NO	SIGNAL NAME
1	VBUS
2	D-
3	D+
4	GND

MATERIALS

HOUSING: THERMOPLASTIC COLOR: BLACK & WHITE(UL 94V-0)
 SHELL: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD FLASH PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C

PART NUMBER

LUB-22AC 04 1 T 1 1HL * 2

SERIES: LUB-22AC
 NO. OF POS.: 04
 CONTACT PLATED OPTION: 1 T
 TRAY PACKAGE: 1 1HL
 TIN PLATING ON SOLDER TAIL: *
 SHELL MATERIALS:
 1:SPCC
 2:COPPER ALLOY
 COLOR:
 1:BLACK
 2:WHITE

		公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		單位/Unit	品名/Title :	鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486	
		.X ±0.30 .XX ±0.20 .XXX ±0.10 ANG. ±3°		mm 比例/Scale Free	USB A TYPE, PCB MOUNT,R/A,METAL SHIELD,FEMALE		
A0	NEW DRAWING	2019.02.18		Size A4	料號/Part No :	圖號/Drawing No :	核加/APPD. 740 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1
REV	概述/REVISION	日期/DATE			LUB-22AC041T11HL_2	22AC-041T-11HLX2(22AC-018)	REV. A0