


Specification:
 Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 1000M Ohm Min. At 500VDC.
 Rated Voltage And Current: 1.5A At 250VAC Minimum.
 Dielectric Withstanding Voltage: 750V AC (rms) for 1 Minute (Rev. 1.1).
 Durability (Life Test): 1500 Cycles.
 Insertion Force: 35 Newton Maximum.
 Extraction Force: 10 Newton Minimum.

NO	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	PBT G.F.	WHITE BLACK	1	P/N: LUBD-KS002A1NWL P/N: LUBD-KS002A1NBL
2	PIN TERM.	PHOS. BRONZE, T:0.25	GOLD-TIN PLATED	8	Gold: 1~3u"; Ni: 40~60u" ; TIN: 120u"
3	SHELL	BRASS, T:0.3	NICKEL PLATED	1	Ni: 80~120u"
4	SPRING CLIP	BRASS, T:0.3	NICKEL PLATED	1	Ni: 80~120u"
5	REAR SHELL	SPCC, T:0.3	NICKEL PLATED	1	Ni: 80~120u"

		公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		單位/Unit mm	品名/Title :	DUAL USB A TYPE 8 PIN		 鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL: (02) 8228-6487 FAX: (02) 8228-6486			
		X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05		比例/Scale Free	料號/Part No :					圖號/Drawing No :	
A0	NEW DRAWING	2019.02.18		Size A4	LUBD-KS002A1N X L		核加/APPD. 7/4	審核/CHKD. Joe	製圖/DR. Mandy	張數/Sheet 1 of 1	REV. A0
REV	概述/REVISION	日期/DATE									