



**Specification:**

- Contact Resistance: 30m Ohm Max.
- Insulation Resistance: 1000M Ohm Min. At 500VDC.
- Rated Voltage And Current: 1.5A At 250VAC Minimum.
- Dielectric Withstanding Voltage: 750V AC (rms) for 1 Minute(Rev. 1.1).
- Durability (Life Test): 1500 Cycles.
- Insertion Force: 35 Newton Maximum.
- Extraction Force: 10 Newton Minimum.

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	PBT G.F.	BLACK	1	
2	PIN TERM.	PHOS. BRONZE,T:0.25	GOLD-TIN PLATED	8	Gold:1~3u"; NI:40~60u"; TIN:120u" (100% pure Tin of lead free plating)
3	SHELL	BRASS,T:0.3	NICKEL PLATED	1	NI: 80~120u"

		公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
		X.	±0.38
		.X	±0.25
A0	NEW DRAWING	.XX	±0.13
REV	概述/REVISION	.XXX	±0.05
		日期/DATE	

單位/Unit	mm	品名/Title :	DUAL USB A TYPE FLAT 8 PIN DIP
比例/Scale	Free	料號/Part No :	LUBD-KS002DA1NBL
Size	A4	圖號/Drawing No :	


**鍊亨電子有限公司**  
 LAI HENG TECHNOLOGY LTD.  
 TEL:(02) 8228-6487 FAX:(02) 8228-6486  
 核加/APPD. Joe 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1