

RECOMMENDED P.C. BOARD PATTERN DIM.

SPECIFICATIONS

Electrical

Voltage Rating: 50VAC DC.

Contact Rating: 1.0A AC DC (AWG 28).

Contact Resistance: Initial value/20 mΩ max;
After environmental testing/40 mΩ max.

Insulator Resistance: 100 MΩ min.

Temperature Range: -25°C to +85°C.

Withstanding voltage: 500V AC/minute.

Material and Finish


Insulator: Nylon 6T, UL94V-0

Insulator Color: Natural.

Contact: Phosphor Bronze, Tin-Plated.

Solder tad: Brass, Copper-undercoated, Tin-Plated.

Circuits	Dimension mm		Part No.
	A	B	
2×10	9.0	13.1	LW-SHD100R-2×10-S
2×15	14.0	18.1	LW-SHD100R-2×15-S
2×20	19.0	23.1	LW-SHD100R-2×20-S
2×25	24.0	28.1	LW-SHD100R-2×25-S

		公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		單位/Unit mm	品名(Title):		 鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL:(02) 8228-6487 FAX:(02) 8228-6486
		.XX ±0.2 .X ±0.3		比例/Scale Free	SMT 90° Type, Dual Row		
A0	NEW DRAWING	2018.08.09		料號/Part No:	圖號/Drawing No:	核准/APPD Joe	審核/CHKD. Mandy
REV	概述/REVISION	日期/DATE		LW-SHD100R-2×XX-S	1001D-2×XX-RT	製圖/DR. Mandy	張數/Sheet 1 of 1
							REV. A0