



SPECIFICATIONS

Electrical

Voltage Rating: 100V AC, DC
 Current Rating: 2A AC, DC
 Withstand Voltage: 800V AC/ min
 Insulation Resistance: 1000MΩ/ min
 Temperature Range: -40°C ~ +85°C

Material

Wafer: High Temperature Plastic Nylon 6T UL94V-0
 Pin: High Strength Brass With Tin Over Nickel Plated
 Applicable PC Board Thickness: 0.8 ~ 1.6mm
 Contact Resistance: Initial Value / 10mΩ max.
 After environmental testing 20mΩ max.

PART NO.	A	B	C
LW-PH200S-02-S	2.00	8.00	4.80
LW-PH200S-03-S	4.00	10.00	6.80
LW-PH200S-04-S	6.00	12.00	8.80
LW-PH200S-05-S	8.00	14.00	10.80
LW-PH200S-06-S	10.00	16.00	12.80
LW-PH200S-07-S	12.00	18.00	14.80
LW-PH200S-08-S	14.00	20.00	16.80
LW-PH200S-09-S	16.00	22.00	18.80
LW-PH200S-10-S	18.00	24.00	20.80
LW-PH200S-11-S	20.00	26.00	22.80
LW-PH200S-12-S	22.00	28.00	24.80
LW-PH200S-13-S	24.00	30.00	26.80
LW-PH200S-14-S	26.00	32.00	28.80
LW-PH200S-15-S	28.00	34.00	30.80
LW-PH200S-16-S	30.00	36.00	32.80

		公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		單位/Unit mm	品名(Title):		鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL: (02) 8228-6487 FAX: (02) 8228-6486
		X.XX ±0.25 X.X ±0.35		比例/Scale Free	2.0mm Wire-to-Board Header SMT 180° SM3 Type		
A0	NEW DRAWING	2018.08.16		Size A4	料號/Part No: LW-PH200S-XX-S		核對/APPD. <i>Zlo</i>
REV	概述/REVISION	日期/DATE			圖號/Drawing No: 2001S-XX-ST		審核/CHKD. <i>Joe</i>
							製圖/DR. <i>Mandy</i>
							報數/Sheet 1 of 1
							REV. A0