



SPECIFICATIONS

Electronical

Current Rating: 2A AC DC

Voltage Rating: 250V AC, DC

Operating Temp.: -25°C ~ +85°C

Contact Resistance: 20mΩ/ Max.

Insulation Resistance: 1000MΩ/ Min.

Withstanding voltage: 800V AC/minute

Material

Material Pin: Brass / Tin-plated

Material: Nylon 66, UL 94V-0+GF

Poles	Dimension mm (in.)		Part No.
	A	B	
4	2.0	6.0	LW-PHD200S-2x02
6	4.0	8.0	LW-PHD200S-2x03
8	6.0	10.0	LW-PHD200S-2x04
10	8.0	12.0	LW-PHD200S-2x05
12	10.0	14.0	LW-PHD200S-2x06
14	12.0	16.0	LW-PHD200S-2x07
16	14.0	18.0	LW-PHD200S-2x08
18	16.0	20.0	LW-PHD200S-2x09
20	18.0	22.0	LW-PHD200S-2x10
22	20.0	24.0	LW-PHD200S-2x11
24	22.0	26.0	LW-PHD200S-2x12
26	24.0	28.0	LW-PHD200S-2x13
28	26.0	30.0	LW-PHD200S-2x14
30	28.0	32.0	LW-PHD200S-2x15
32	30.0	34.0	LW-PHD200S-2x16
34	32.0	36.0	LW-PHD200S-2x17
40	38.0	42.0	LW-PHD200S-2x20

A0	NEW DRAWING	2018.08.16
REV	概述/REVISION	日期/DATE

公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 X.XX ±0.25
 X.X ±0.35

單位/Unit mm
 比例/Scale Free
 Size A4

品名(Title): **2.0mm Wire-to-Board Header 180° Dual Row Type**
 料號/Part No: **LW-PHD200S-2xXX**
 圖號/Drawing No: **2001D-XX-ST**

鍊亨電子有限公司
 LAI HENG TECHNOLOGY LTD.
 TEL: (02) 8228-6487 FAX: (02) 8228-6486

核對/APPD. Joe 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 2

REV. A0