



SPECIFICATIONS

Current rating : 2A AC,DC
 Voltage rating : 250V AC,DC
 Temperature range : -25°C to +85 °C
 Contact resistance : 20mΩ Max.
 Insulation resistance : 1000MΩ Min.
 Withstanding voltage : 800V AC/minute
 Terminal Material : Brass/ Tin-plated
 Material : Nylon 66, UL94V-2

Ordering Information & Dimensions

Poles	Dimension (mm)		Part No.
	A	B	
02	2.50	5.10	LW-DP250S-02
03	5.00	7.60	LW-DP250S-03
04	7.50	10.10	LW-DP250S-04
05	10.00	12.60	LW-DP250S-05
06	12.50	15.10	LW-DP250S-06
07	15.00	17.60	LW-DP250S-07
08	17.50	20.10	LW-DP250S-08
09	20.00	22.60	LW-DP250S-09
10	22.50	25.10	LW-DP250S-10

PART NO.:
LW-DP 250 S - XX

No.Of Contact:02~10
 Angle Type: Straight Angle (180°)
 Pitch:2.50mm
 Wafer Series No.

公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit mm	品名(Title): 2.5mm Wire-to-Board Header DIP 180° Type	 LAI HENG TECHNOLOGY LTD. TEL: (02) 8228-6487 FAX: (02) 8228-6486
A0	NEW DRAWING	2018.08.16	比例/Scale Free	料號/Part No: LW-DP250S-XX	
REV	概述/REVISION	日期/DATE	Size A4		核對/APPD. Joe
					審核/CHKD. Joe
					製圖/DR. Mandy
					報數/Sheet 1 of 1
					REV. A0