



Specifications

Electrical

Voltage Rating: 100V(AC)

Current Rating: 2A

Contact Resistance: 20mΩ max.

Dielectric Withstandeing Voltage: 800V AC/1min.

Insulation Resistance: 1000MΩ min.

Material

Circuits: 2~16

Insulator: Nylon 66 UL 94V-0

Color: White

Contact: Brass 0.50mm(0.20") Square Pin

Plating: Tin Plated

Temperature Range: -25° C~+85° C

Applicable PC Board Thickness: 0.8 to 1.6mm

PART NO.:
LW-PH 200 S - XX

Insulation Color:
Blank:White (Standard)
B:Black , BL:Blue
R:Red , Y:Yellow

No.Of Contact:
02~16

Type: Straight

Pitch: 2.00mm

Wafer Series No.

Poles	Dimension mm (in.)		Note.
	A	B	
2	2.0(0.079)	6.1(0.240)	
3	4.0(0.157)	8.1(0.318)	
4	6.0(0.236)	10.1(0.397)	
5	8.0(0.315)	12.1(0.476)	
6	10.0(0.394)	14.1(0.555)	
7	12.0(0.472)	16.1(0.634)	
8	14.0(0.551)	18.1(0.713)	
9	16.0(0.630)	20.1(0.791)	
10	18.0(0.709)	22.1(0.870)	
11	20.0(0.787)	24.1(0.949)	
12	22.0(0.886)	26.1(1.028)	
13	24.0(0.945)	28.1(1.106)	
14	26.0(1.024)	30.1(1.185)	
15	28.0(1.102)	32.1(1.263)	
16	30.0(1.181)	34.1(1.343)	

			公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	單位/Unit mm	品名(Title):
A0	NEW DRAWING	2018.06.11	X.XX ±0.2 X.X ±0.3	比例/Scale Free	2.0mm Wire-to-Board Header DIP 180° Type
REV	概述/REVISION	日期/DATE		Size A4	料號/Part No.: LW-PH200S-XX

鍊亨電子有限公司
LAI HENG TECHNOLOGY LTD.
TEL: (02) 8228-6487 FAX: (02) 8228-6486

核對/APPD. 7/6 審核/CHKD. Joe 製圖/DR. Mandy 張數/Sheet 1 of 1

REV. A0