



SPECIFICATIONS

Electrical

- Current Rating: 2A AC DC
- Voltage Rating: 250V AC, DC
- Operating Temp.: -25°C ~ +85°C
- Contact Resistance: 20mΩ/ Max.
- Insulation Resistance: 1000MΩ/ Min.
- Withstanding voltage: 800V AC/minute

Material

- Material Pin: Brass / Tin-plated
- Material: Nylon 66, UL 94V-0+GF

Poles	Dimension mm (in.)		Part No.
	A	B	
4	2.0	6.0	LW-PHD200R-2x02
6	4.0	8.0	LW-PHD200R-2x03
8	6.0	10.0	LW-PHD200R-2x04
10	8.0	12.0	LW-PHD200R-2x05
12	10.0	14.0	LW-PHD200R-2x06
14	12.0	16.0	LW-PHD200R-2x07
16	14.0	18.0	LW-PHD200R-2x08
18	16.0	20.0	LW-PHD200R-2x09
20	18.0	22.0	LW-PHD200R-2x10
22	20.0	24.0	LW-PHD200R-2x11
24	22.0	26.0	LW-PHD200R-2x12
26	24.0	28.0	LW-PHD200R-2x13
28	26.0	30.0	LW-PHD200R-2x14
30	28.0	32.0	LW-PHD200R-2x15
32	30.0	34.0	LW-PHD200R-2x16
34	32.0	36.0	LW-PHD200R-2x17
40	38.0	42.0	LW-PHD200R-2x20

		公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		單位/Unit mm	品名(Title):		鍊亨電子有限公司 LAI HENG TECHNOLOGY LTD. TEL: (02) 8228-6487 FAX: (02) 8228-6486
		X.XX ±0.25 X.X ±0.35		比例/Scale Free	2.0mm Wire-to-Board Header 90° Dual Row Type		
A0	NEW DRAWING	2018.08.16		尺寸/Size A4	料號/Part No:	圖號/Drawing No:	核對/APPD. Joe
REV	概述/REVISION	日期/DATE			LW-PHD200R-2xXX	2001D-XX-RT	製圖/DR. Manly
							報數/Sheet 1 of 2
							REV. A0